



6' Compact Retractable
Lightweight safety in the palm of your hand



Quick locking action for low clearance applications



Combine two units for a twin leg, 100% tie-off solution



Lightweight, compact, durable

NEW

Class A <24" arrest distance & <900 lb arrest force



6' Compact Retractable



Carabiner
Connects device to harness in single leg application

Swivel Anchor Loop
Limits lifeline twisting for smooth operation

Impact-Resistant Housing
high-strength housing maximizes durability

Shock Absorber
integrated impact absorber

3600lb Gate



Twinleg Carabiner Adaptor connects through webbing under harness D-ring

- Quick Locking Action for low clearance applications
- Meets ANSI z359.14 CLASS A <24" arrest distance requirement while keeping average arrest force <900 lbs.
- Extremely compact and lightweight at less than 2.5 lbs
- 310 lb rated capacity
- Maximum arrest distance of 24"
- Achieve 100% tie-off configuration by making a twin-leg self-retracting lifeline.



R430006



R431006



R430006-R



R431006-R

*not for use in leading edge applications

| Model# | Lifeline Length | Lifeline Material | Housing Material | Lifeline Connector | Anchorage Connector | Weight | Standard Compliance |
|-----------|-----------------|-----------------------|------------------------------|--------------------|---------------------|----------|---|
| R430006 | 6' | Dyneema/ Polyester | Impact Resistant Nylon | Snap Hook | Carabiner | 2.3 lbs. | ANSI z359.14, Class A (24") OSHA 1910 & 1926 |
| R430006-R | 6' | | | Al Rebar | Carabiner | 2.5 lbs. | |
| R431006 | Twinleg 6' | | | Snap Hook | Twinleg Carabiner | 5.5 lbs. | |
| R431006-R | Twinleg 6' | | | Al Rebar | Twinleg Carabiner | 5.7 lbs. | |

www.wernerfallprotection.com

Werner Co. • 93 Werner Road • Greenville, PA 16125

888-523-3371 • FAX 888-456-8459