



PERRY JOHNSON LABORATORY ACCREDITATION, INC.

Certificate of Accreditation

Perry Johnson Laboratory Accreditation, Inc. has assessed the Laboratory of:

Werner Co.

Av. Tagushi #251 Parque Industrial North Gate, Ciudad Juarez, Chih Mexico

(Hereinafter called the Organization) and hereby declares that Organization is accredited in accordance with the recognized International Standard:

ISO/IEC 17025:2017

This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (as outlined by the joint ISO-ILAC-IAF Communiqué dated April 2017):

Mechanical Testing *(As detailed in the supplement)*

Accreditation claims for such testing and/or calibration services shall only be made from addresses referenced within this certificate. This Accreditation is granted subject to the system rules governing the Accreditation referred to above, and the Organization hereby covenants with the Accreditation body's duty to observe and comply with the said rules.

For PJLA:

Tracy Szerszen
President

Perry Johnson Laboratory
Accreditation, Inc. (PJLA)
755 W. Big Beaver, Suite 1325
Troy, Michigan 48084

Initial Accreditation Date:

January 26, 2015

Issue Date:

June 9, 2021

Expiration Date:

September 30, 2023

Accreditation No.:

74893

Certificate No.:

L21-353

The validity of this certificate is maintained through ongoing assessments based on a continuous accreditation cycle. The validity of this certificate should be confirmed through the PJLA website: www.pjilabs.com



Certificate of Accreditation: Supplement

Werner Co.

Av. Tagushi #251 Parque Industrial North Gate, Ciudad Juarez, Chih, Mexico
Contact Name: Brett Latimer Phone: 724-588-2000

Accreditation is granted to the facility to perform the following testing:

FIELD OF TEST	ITEMS, MATERIALS OR PRODUCTS TESTED	SPECIFIC TESTS OR PROPERTIES MEASURED	SPECIFICATION, STANDARD METHOD OR TECHNIQUE USED	RANGE (WHERE APPROPRIATE) AND DETECTION LIMIT
Mechanical ^F	Fall Protection Products	Dynamic Performance	ANSI Z359.1	Drop Test between 0.5 ft to 20 ft
		Dynamic Strength	ANSI Z359.3	
		Static Strength	ANSI Z359.4	Test Weight between 5 lb to 430 lb
		Activation Force	ANSI Z359.11	
		Arrest Distance	ANSI Z359.14	Force Measurement 0.1 lbf to 10 000 lbf
		Elongation	ANSI Z359.18	
		Slippage		Conditioning RH 20 % to 95 %
		Angle at Rest		
		Retraction Tension		Temperature between -70 °C to 180 °C
			Angle 0.1° to 90°	
			Peak Impact Loads 0.1 lbf to 10 000 lbf	

1. The presence of a superscript F means that the laboratory performs testing of the indicated parameter at its fixed location. Example: Outside Micrometer ^F would mean that the laboratory performs this testing at its fixed location.